

安全データシート

整理番号 No.1070

作成 2013年08月19日 改訂 2021年06月01日

1. 化学物質等及び会社情報

製品名 パックテスト 3価鉄 型式 WAK-Fe³⁺

会社名 株式会社共立理化学研究所

住所 〒226-0006 神奈川県横浜市緑区白山1-18-2 ジャーマンインダストリーパーク

電話番号 045-482-6937

F A X 045-507-3418

担当部署 営業部

用途と使用上の制限 水質測定用の試薬

2. 危険有害性の要約

【GHS分類】

物理化学的危険性：分類できない(GHS分類に必要なデータなし)

健康有害性：

皮膚腐食性／刺激性： 区分1

眼に対する重篤な損傷性／眼刺激性： 区分1

上記で記載がない健康有害性の項目は、すべて区分外または分類できない(GHS分類に必要なデータなし)

環境有害性：分類できない(GHS分類に必要なデータなし)

【GHSラベル要素】



【注意喚起用語】

危険

【危険有害性情報】

重篤な皮膚の薬傷・眼の損傷

重篤な眼の損傷

【注意書き】

試薬は子どもの手の届かない乾暗所（常温）に保管すること。

使用前に使用法をよく読み、記載以外の使い方をしないこと。

必要に応じて個人用保護具を使用すること。

試薬を吸入しないこと。

汚染された衣類は洗濯すること。

取扱い前後はよく手を洗うこと。

環境への放出を避けること。

3. 組成、成分情報

単一製品・混合物の区別：混合物

試薬名	K-1試薬	
化学名	5-スルホサリチル酸二水和物	ホルエチレン
含有量	< 10%	> 90%
化学式	C ₆ H ₃ (OH)(SO ₃ H)COOH · 2H ₂ O	(C ₂ H ₄) _n
官報公示 整理番号	3-2114	(6)-1
CAS No.	5965-83-3	9002-88-4

4. 応急措置

試薬や測定液が

眼に入った場合 : 直ちに15分以上、よく洗眼する。その後、直ちに眼科医の診断を受ける。

皮膚に付いた場合 : 直ちに多量の水でその部分をよく洗い流す。

口に入った場合 : 直ちに多量の水で口の中をよく洗い流す。

上記の措置後に異常があった場合には、直ちに医師の手当を受ける。

特に試薬や測定液を飲み込んでしまった場合には、多量の牛乳または水を飲み、直ちに医師の手当を受ける。

5. 火災時の措置

消火方法 : 火元への燃焼源を断ち、消火剤を使用して消火する。

消火剤 : 水(噴霧)、粉末消火薬剤、炭酸ガス、乾燥砂

6. 漏出時の措置

屋外では、試薬や廃液がこぼれないよう注意する。

屋内では、机面・床面等に試薬や廃液がこぼれた場合は直ちに拭き取り、廃棄する。その際、眼や皮膚に触れないようにする。

濃厚廃液が下水道や河川等の周辺環境に流出しないように注意する。

7. 取扱い及び保管上の注意

取扱い : 試薬や測定液は、pH2以下の酸性であるので、眼や皮膚に触れたり吸い込んだりしないようにする。特にチューブ内の粉末試薬は吸い込まないように注意する。

また、屋外での使用時には、試薬および測定後の廃液、使用済み容器は必ず持ち帰る。

保管 : 直射日光を避け、換気のよい乾暗所(常温)に保管する。

8. 暴露防止及び保護措置

管理濃度(作業環境評価基準) : 設定されていない。

許容濃度(日本産業衛生学会) : 設定されていない。

(ACGIH(TLV(s))) : 設定されていない。

(OSHA(PEL)) : 設定されていない。

保護具 : 保護眼鏡・保護手袋等の使用が望ましい。

9. 物理的及び化学的性質

物理的状態 : 粉末入りチューブ 1.1g× 50本/キット 5本ずつアルミラミネート包装

試薬の色 : 白色(粉末)、半透明(ポリエチレンチューブ)

試薬の臭い : なし

測定 pH : 2以下

混合物として融点、沸点、引火点、発火点、爆発限界下限、蒸気圧、密度、比重、溶解性、Pow、動粘性率等のデータなし。

10. 安定性及び反応性

高温、多湿、直射日光下への放置を避ける。

通常の使用条件では安定であり、特定条件下で生じる危険な反応もなし。危険有害な分解生成物についてのデータなし。

11. 有害性情報

混合物についてのデータはない。個別物質について記す。

5-スルホサリチル酸二水和物：

急性毒性(経口)：経口摂取すると、悪心、嘔吐、腹痛、耳鳴りなどを起こす。

ラットLD₅₀ = 2450mg/kg

ウサギLDL₀ = 1300mg/kg

その他の項目についてのデータなし。

ホリエチレン：

急性毒性(経口)：経口-ラット LD₅₀ > 7、950mg/kg (下記、ATEmix値算出時は7、950mg/kgとして計算)

発がん性：IARCのグループ 3 (ヒトに対する発がん性は評価できない。)

その他の項目についてのデータなし。

以下、GHS分類判定について記す。

[皮膚腐食性/刺激性]：混合物のpHが2以下である。

よって、区分1 (危険、重篤な皮膚の薬傷・眼の損傷) に分類される。

[眼に対する重篤な損傷性/眼刺激性]：混合物のpHが2以下である。

よって、区分1 (危険、重篤な眼の損傷) に分類される。

[急性毒性(経口)]、[急性毒性(経皮)]、[呼吸器感作性または皮膚感作性]、[生殖細胞変異原性]、[発がん性]、

[生殖毒性]、[特定標的臓器毒性(単回暴露)]、[特定標的臓器毒性(反復暴露)]、[吸引力呼吸器有害性]

以上の項目は、区分外または含有成分のデータがそろっていないため、分類できない。

12. 環境影響情報

混合物についてのデータはない。個別物質について記す。

5-スルホサリチル酸二水和物、ホリエチレン：環境影響情報についてのデータなし。

以下、混合物としてGHS分類判定について記す。

[水生環境有害性 短期 (急性)]、[水生環境有害性 長期 (慢性)]

以上の項目は、含有成分のデータがそろっていないため、分類できない。

[海洋層への有害性]

含有成分がモトリオール議定書の附属書に列記されていないため、分類できない。

13. 廃棄上の注意

測定後の廃液は pH2 以下の酸性である。

事業活動で使用する場合は、各関係法令に従って適切に廃棄する。

それ以外の場合は、残余廃棄物や使用済み容器はそのまま「燃やすゴミ」としての廃棄も推奨する。

14. 輸送上の注意

取扱い及び保管上の注意の項の記載による他、容器が破損しないように乱暴な取扱いを避ける。また、長距離の輸送の場合は、長時間の高温状態は試薬の劣化が考えられるため、航空機による輸送が望ましい。

国連分類・番号	該当せず。
航空法	該当せず。
消防法	該当せず。
製品総重量	約140g/キット

15. 適用法令

毒物及び劇物取締法： 該当せず。

PRTR法： 該当せず。

労働安全衛生法： 該当せず。

廃棄物の処理及び清掃に関する法律： 測定後の廃液はpH2以下であり、同法上の特別管理産業廃棄物に該当する。

16. その他の情報

引用・参考文献

- 15、911の化学商品、化学工業日報社(2011)
製品安全データシート No.JW190457、和光純薬工業株式会社(2011.10.19)
製品安全データシート No.37384、関東化学株式会社(2004.01.15)
製品安全データシート No.051110033、東ソー株式会社(2004.07.09)
国土交通省航空局監修、航空危険物輸送法令集、鳳文書林出版販売(2019)
JIS Z 7252:2019 GHSに基づく化学物質等の分類方法(日本工業標準調査会 審議)
JIS Z 7253:2019 GHSに基づく化学品の危険有害性情報の伝達方法ーラベル 作業場内の表示及び安全データシート(SDS)(日本工業標準調査会 審議)
GHS 国連文書(仮訳 改訂4版)、GHS 関係省庁連絡会議(2011)
経済産業省、事業者向け GHS 分類ガイド(平成 25 年度改訂版)(2013)

- 注) この情報は、必ずしも充分ではないので、取扱いには注意をお願いします。
本データシートは情報を提供するもので記載内容を保証するものではありません。
新しい知見やそれに伴う従来の考え方の修正等により、記載内容に変更が生じることがあります。
なお、注意事項は通常の実施を対象としております。

Safety Data Sheet

Reference No. 1070

Issue: 19th August 2013
Revision: 1st June 2021

1. Chemical product and company identification

Product name	PACKTEST Iron (Trivalent)	Model	WAK-Fe ³⁺
Company name	KYORITSU CHEMICAL-CHECK Lab., Corp.		
Address	1-18-2 Hakusan, Midori-ku, Yokohama, Kanagawa 226-0006, JAPAN		
Tel	+81-45-482-6937		
Fax	+81-45-507-3418		
Dept. in charge	Sales Department		

Recommended uses and restrictions Reagent for water quality measurement

2. Hazards identification

[GHS Classification]

Physical hazards: Classification not possible (no data for GHS classification available)

Health hazards:

Skin corrosion/ irritation: Category 1

Serious eye damage/ eye irritation: Category 1

For those health hazards not listed above are not classified or classification not possible (no data for GHS classification available)

Environmental hazards: Classification not possible (no data for GHS classification available)

[GHS labeling elements]



[Signal word]

Danger

[Hazard statements]

Causes severe skin burns and eye damage.

Causes serious eye damage.

[Precautionary statements]

Keep out of reach of children and store in the dry and dark place at room temperature.

Carefully read instructions before use and do not use for other purposes.

Wear personal protective equipment if necessary.

Do not inhale reagents.

Wash contaminated clothing.

Wash hands well before and after handling.

Avoid release to the environment.

3. Composition/ information on ingredients

Discrimination of single substance or mixture: Mixture

Reagent name	K-1 reagent	
Chemical name	5-Sulfosalicylic acid dihydrate	Polyethylene
Content	< 10%	> 90%
Chemical formula	C ₆ H ₃ (OH)(SO ₃ H)COOH · 2H ₂ O	(C ₂ H ₄) _n
METI No. (reference number under CSCL in Japan)	3-2114	(6)-1
CAS No.	5965-83-3	9002-88-4

4. First-aid measures

If reagents or test solutions;

Enter in eyes: Immediately rinse with water for more than 15 minutes followed by the treatment by an ophthalmologist.

Contact with skin: Immediately wash out contaminated site with plenty of water.

Enter into mouth: Immediately rinse mouth with plenty of water.

If any symptoms appear after above measures, immediately get medical advice or treatment.

Especially in case ingested reagents or test solutions, immediately drink plenty of water or milk and immediately get medical advice or treatment.

5. Fire-fighting measures

Extinguishing methods: Cut off ignition sources and extinct by a suitable media.

Suitable extinguishing media: Water (mist), powder, carbon dioxide, dry sand.

6. Accidental release measures

In case of outdoor use: avoid spill of reagents and waste solutions.

In case of indoor use: if spilled on a table or floor, wipe off immediately spilled reagents and dispose of them. Do not contact with eyes and skin.

Concentrated waste solution should not be released into sewer or rivers.

7. Handling and storage

Handling: Avoid contact of the reagents with eyes and skin. Do not ingest or inhale the reagents. It needs special attention because pHs of K-1 reagent and waste solutions after the measurement are lower than 2, acidic.

Especially for outdoor use, ensure to bring back reagents, waste solutions after the measurement and used containers.

Storage: Avoid direct sunlight and store in a well-ventilated, dry and dark place at room temperature.

8. Exposure controls and personal protection

Administrative control level

Working environment standard: Not established

Occupational exposure limits

Japan Society for Occupational health: Not established

ACGIH (TLVs): Not established

OSHA (PEL): Not established

Protective equipment: Recommended to wear protective glasses and gloves

9. Physical and chemical properties

Physical state: Tube containing powder reagent 1.1 g x 50 tubes/kit, (5 tubes per one aluminum laminated packaging)
Color: White (powder), Semi-transparent (polyethylene tube)
Odor: No odor
pH: <2

Melting point, boiling point, flash point, ignition point, lower explosion limit, vapor pressure, density, specific gravity, solubility, Pow, kinetic viscosity: not available as a mixture

10. Stability and reactivity

Avoid leaving in a place where high temperature, humid or under direct sunlight. Stable under normal use conditions and no dangerous reactions under specific conditions are expected. No information on hazardous decomposition product is available.

11. Toxicological information

No data on mixture is available. Data on each substance are shown below.

5-Sulfosalicylic acid dihydrate:

Acute toxicity: If swallowed, cause nausea, vomiting, abdominal pain, and ringing in the ears.

Oral: Rat LD₅₀ = 2450mg/kg

Oral: Rabbit LD₀ = 1300mg/kg

Other data: Not available

Polyethylene:

Acute toxicity:

Oral: Rat LD₅₀ > 7,950 mg/kg

Carcinogenicity: IARC Group 3 (not classifiable as to carcinogenicity to humans).

Other data: Not available

GHS classifications as a mixture are shown below.

[Skin corrosion/ irritation],

Classified as Category 1 (Danger, Causes severe skin burns and eye damage.) because pH of mixture is lower than 2.

[Serious eye damage/ eye irritation]

Classified as Category 1 (Danger, Causes serious eye damage.) because pH of mixture is lower than 2.

[Acute toxicity (oral)], [Acute toxicity (dermal)], [Respiratory or skin sensitization], [Germ cell mutagenicity], [Carcinogenicity], [Reproductive toxicity], [Specific target organ toxicity (single exposure)], [Specific target organ toxicity (repeated exposure)], [Aspiration hazard]

Not classified or classifications are not possible because of data lack.

12. Ecological information

No data on mixture is available. Data on each substance are shown below.

5-Sulfosalicylic acid dihydrate, Polyethylene: No eco-toxicological information available.

GHS classifications as a mixture are shown below.

[Hazardous to the aquatic environment, short-term (acute)],

[Hazardous to the aquatic environment, long-term (chronic)]

Classifications are not possible because of data lack.

[Harmful effects on the ozone layer]:

Classification is not possible because each of the substances is not described in Annex to Montreal Protocol.

13. Disposal considerations

pH of waste solution in tube is lower than 2(acid).

Always dispose of in accordance with local regulations.

14. Transport information

In addition to precautionary measures regarding handling and storage, avoid rough handling so as not to break containers. It is recommended to ship by air because under high temperature for long period may lead to deterioration.

UN classification and number: Not applicable
Civil Aeronautics Act: Not applicable
Fire Service Act: Not applicable
Total weight of the product: ca.140 g/kit

15. Regulatory information

Poisonous and Deleterious Substances Control Act: Not applicable
PRTR Act: Not applicable
Industrial Safety and Health Act: Not applicable
Waste Disposal and Cleaning Act: Applicable
pH of waste solution after the measurement is less than 2 and is applicable as Special Controlled Industrial Waste under the Act.

16. Other information

Reference literature

15,911 no Kagaku Shouhin, The Chemical Diary Co., Ltd. (2011)
Material Safety Data Sheet No.JW190457, Wako Pure Chemical Industries, Ltd. (2011.10.19)
Material Safety Data Sheet No.37384, KANTO CHEMICAL CO., INC. (2004.01.15)
Material Safety Data Sheet No.051110033, TOSOH CORPORATION (2004.07.09)
Koukuu Kikenbutsu Yusou Houreisyu, Ed. MLIT, HOUBUN SHORIN CO., LTD. (2019)
JIS Z 7252:2019 Classification of chemicals based on "Globally Harmonized System of Classification and Labelling of Chemicals (GHS)" (Japanese Industrial Standards Committee)
JIS Z 7253:2019 Hazard communication of chemicals based on GHS-Labeling and Safety Data Sheet (SDS) (Japanese Industrial Standards Committee)
UN GHS (tentative translation, forth revised version), GHS Kankei Syocho Renraku Kaigi (2011)
Ministry of Economy, Trade and Industry, GHS Classification Guidance for Enterprises 2013 Revised Edition (2013)

NOTE) This information is not always exhaustive and use with care.
This data sheet only provides information but any description cannot be warranted.
Descriptions may possibly be changed because of new findings or modification of the current knowledge.
Precautions only cover normal handling.
This English SDS is prepared in the cooperation with the Chemicals Evaluation and Research Institute (CERI), Japan.